JEFFERSON COUNTY PLANNING DEPARTMENT



445 W. PALMER MILL ROAD - MONTICELLO, FLORIDA 32345 Phone (850) 342-0223 - Fax: (850) 342-0225

ROAD & DRIVEWAY CONNECTION PACKET

All <u>new</u> road or driveway connections to a County-maintained road shall be required to obtain a Jefferson County Driveway Connection Permit. This process will ensure the Road Department:

- 1. Is aware of all vehicular connections to the County-maintained roadway system;
- 2. Will determine if a culvert will be required at the connection to the County Road to ensure the continued function of the County Road drainage system.
- 3. To inspect and determine the culvert was installed correctly.

DRIVEWAY CONNECTION PERMITS WILL NOT BE REQUIRED:

- Additions To Existing Structures
- Accessory Structures Where A Driveway Exists
- Connections To A Private Road.

The permit fee is: \$53.00

Make checks payable to: Jefferson County Board of County Commissioners

Notify the Road Department at least 24 hours prior to the requested date of inspection.

REQUIRED INFORMATION:

Owner Name:				
Current Mailing Address:				
City:	State			
Driveway 911 Address:				
Tax ID #:				
Phone #:	Name of County road:			
Purpose of driveway (CHECI	CONE): Residential, Commercial, Development			
If a new Development, appro	ved name of new road:			
 Attach a recorded co Draw or attach a sin 	opy of the warranty deed. uple location map.			
3. Stake the middle of proposed driveway with white flagging material.				
4. Provide any special instructions, information, or markings below:				

Last Edited: 5/19/2020

Jefferson County Road Department 1484 S. Jefferson Monticello, FL 32344 Telephone (850)997-2036 Fax (850)997-6760 AGENT AUTHORIZATION FORM

For obtaining driveway connection permit

To: Jefferson County Road Department	Date:
Property legal description: (Please attach	copy of deed)
	of above property, do hereby grant permission to to obtain the necessary permit for a driveway from the r to the day of closing.
Phone number to reach owners	,
_	
Printed name of owner	Signed name of owner
STATE OF FLORIDA, COUNTY OF	F JEFFERSON
Signed before me this day of	
who is \square personally known to me or \square	who producedidentification
Signature	Stamp:

Jefferson County Road Department 1484 S. Jefferson Monticello, FL 32344 Telephone (850)997 - 2036 Fax (850)997 6760

Written directions from Courthouse Circle to Proposed driveway location: **DRAW MAP BELOW Show North Direction**

Driveway Culvert Installation & Permit Procedures

- 1. All driveways or roads entering a County road right of way shall have a driveway culvert installed when necessary to facilitate roadway drainage.
- 2. The driveway connection shall slope away from the roadway edge at a minimum grade of 2% from the edge of the road pavement to the centerline of the culvert pipe to ensure runoff from the driveway will not cross the County-maintained road. Property owner may be required to install slotted pipe to prevent storm water draining into County roadway.
- 3. The Road Department Superintendent or his representative shall determine the appropriate pipe diameter and flow line of the new driveway culvert.
- 4. The overall pipe length shall be at least the driveway width plus the length required to provide for mitered end sections. Mitered end sections with 4:1 slope are required unless a variance is granted by written permission from the Road Superintendent.
- 5. The pipe material shall be reinforced concrete pipe on all roads, except corrugated metal may be utilized with written permission from the Road Superintendent.
- 6. A private contractor will install driveway culverts:
 - (a) A valid permit must be issued.
 - (b) The property owner or the contractor will supply the pipe specified by the Road Superintendent or his representative.
 - (c) The property owner pays all costs.
- 7. The depth of the existing ditch shall be defined as the vertical height as measured from the edge of the existing road pavement to the bottom of the existing ditch. The Road Department will adjust ditches if needed.
- 8. The pipe shall be backfilled with clean fill dirt.
- 9. Driveway connections that connect to a paved road shall be required to pave the aprons with concrete or asphalt. The driveway apron is the area between the edge of the road surface and the right of way or 30' from the road centerline on County-maintained roads where there is no defined right of way boundary.
- 10. **Note**: If a private contractor installs the driveway culvert, the Road Superintendent must be called to inspect the installation before the contractor can backfill the trench. Failure to have the installation inspected prior to backfilling may result in the Road Department removing the driveway culvert.
- 11. The Road Department Superintendent or his representative will inspect the culvert at the request of the property owner or his authorized representative/agent.
- 12. Driveways connecting to State and/or County roads shall follow the most current standards depicted in FDOT INDEX 273 -SIDE DRAIN MITERED END SECTIONS, which can be found online at http://www.dot.state.fl.us/rddesign/DS/12/IDx/00273.pdf.

Last Edited: 5/19/2020

Name:		Project Address if Different from	
		Address:	
		Liden ballet	* *
To construct and maintain	ı a	by laying(length)	feer of
		East () South () West side of	
(road)	approximately	feel () North () East () S	South () West
of(nearest interscoling	and	leet from edge of road.	(4)
INDICATE NORTH	· · ·	Centerline d	
. *			R-O-W
Distance from Edge of Ad		Proposed pipe radius	
Centerline of county;	oad	5 may 5 5 may 5 5 may 5 5 may 5 6 may 5 6 may 7 8 5 may 5 5 may 6 5 may 6 6 may 1 5 ma	<u> </u>
		en tien men men and and peut men were tota dare was mile mile dell tien dare	book area and than took took after pure tast on
Sample Site Plan for Drivewa Resurface	y Culvert and	**	





